

**MOLYCOTE 3400 A ®****Description**

Coating made of a dispersion of solid lubricants and corrosion inhibitors in a thermoset resin

**General properties**

The main properties are the corrosion protection of surfaces of bearings and hte excellen lubrication. It isw specially for applications on:

- High loads
- Low speed
- Dirty and abrasive environments
- Couplings of surfaces not accesible to relubrication
- For a new or reconstructed equipment

**Uses**

It is used mainly in:

- Aerospace application (door latches, bearings sleeve type, leavers, oscillating bearings and splines)
- Automotive applications (pins, springs and bearing surfaces on brakes, hinge pins, selectors)
- Construction equipmen (hinges, friction bushings, truck chassis)



**THIS TREATMENT IS APPLIED DIRECTLY IN LINE OR IN COMBINATION WITH PREVIOUS AND SUBSEQUENT APPLICATIONS.**  
**GALOL S.A. offers the possibility to reduce logistic costs between the different operations of manufacturing of the part.**

**Application technology****Dip-spinning****Standards and specs**

- MIL-L46010 A
- TL 241

**GALOL S.A.**

Camino de Montaverner, s/nº  
 E 46850 L'Olleria (Valencia)  
 Tel. 962 208 005  
 Http: www.galol.com  
 E-mail: galol@galol.com

